

PALLET TRUCK

STAND ON TYPED



Guangxi LiuGong Machinery Co.,Ltd.
No. 1 Liutai Road, Liuzhou, Guangxi.
545007
PR China
T: +86 0772 3886124
E: overseas@liugong.com
HQ: www.liugong.com
MH: www.lgforklift.cn

Like and follow us:



LIUGONG 082019-ENG

The LiuGong series of logos herein, including but not limited to word marks, device marks, letter of alphabet marks and combination marks, as the registered trademarks of Guangxi LiuGong Group Co., Ltd. are used by Guangxi LiuGong Machinery Co., Ltd. with legal permission, and shall not be used without permission. Specifications and designs are subject to change without notice. Illustrations and pictures may include optional equipment and may not include all standard equipment. Equipment and options varies by regional availability.

TOUGH WORLD. TOUGH EQUIPMENT.

Electric Pallet Truck

Main Features

POWERFUL

- **Powerful AC-drive unit** from the global industry leaders. the AC driving motor designed and produced by **Schabmuller** comes together with the top quality **ZF** gearbox and it is equipped with **Intorq** electromagnetic brake. The drive unit can provide the drive speed up to **8km/h**. The use of top level quality **drive wheels** helps to ensure the **long life time** of PU tires.



RELIABLE

- The **driving controllers and steering controllers** are manufactured by **Zapi**(Italy)-the leading European brand with long history in the industry, which provides extremely reliable and flexible solutions with high performance level of the control system.



COMFORTABLE

- The model range can be equipped with the **option of Electric Power Steering(EPS)** which delivers precise and fast control for the position of steering wheel and has a high level of reliability as well as safety according to official standards.



ERGONOMICS

- The **Germany Rema tiller** delivers high level of **ergonomics** as well as **reliability** of control system. In addition, the tiller ensures a long-life-time thanks to the contactless rocker switches designed for lifting/lowering function.



FLEXIBLE

- The **integrated design of operator's platform and protective arms** as well as totally new internal structure allows to ensure the smallest body length of the stackers and provide **extremely low turning radius** among competitors. Together with this, the suspension system for the platform helps to provide the **high level of comfort** to operators.



SPECIFICATION

Feature	Model	1	CLG2020L-R3	CLG2025L-R3	
	Power Type	2	Electric		
Driving Type	3	Standing			
Capacity	4	kg	2000	2500	
Dimension	Overall Length	5	mm	1790	1895
	Overall Wide	6	mm	790	
	Overall Height	7	mm	1350	
	Min. Height of Fork	8	mm	85	
	Max. Height of Fork	9	mm	205	
	Fork	10	mm	1150×173×55	
	Fork Spread	11	mm	540 / 685	
	Wheel Base	12	mm	1330	1435
	Turning Radius	13	mm	1585	1690
	Performance	Driving Speed (load / unload)	14	km/h	7.0 / 8.0
Lifting Speed (load / unload)		15	mm/s	25 / 30	35 / 45
Lowering Speed (load / unload)		16	mm/s	30 / 25	45 / 50
Motor	Driving Motor Power	17	kw	1.4	
	Lifting Motor Power	18	kw	0.8	2.2
	Battery Capacity / Voltage	19	Ah/v	210 / 24	270 / 24
Wheel Dimension	Front Wheel	20	mm	Φ84×84	
	Balance Wheel	21	mm	Φ100×40	
	Driving Wheel	22	mm	Φ210×70	
Weight	Service Weight	23	kg	650	770
	Battery	24	kg	185	235

