

REACH TRUCK

STANDING TYPED



Guangxi LiuGong Machinery Co.,Ltd.
No. 1 Liutai Road, Liuzhou, Guangxi.
545007
PR China
T: +86 0772 3886124
E: overseas@liugong.com
HQ: www.liugong.com
MH: www.lgforklift.cn

Like and follow us:



LIUGONG 082019-ENG

The LiuGong series of logos herein, including but not limited to word marks, device marks, letter of alphabet marks and combination marks, as the registered trademarks of Guangxi LiuGong Group Co., Ltd. are used by Guangxi LiuGong Machinery Co., Ltd. with legal permission, and shall not be used without permission. Specifications and designs are subject to change without notice. Illustrations and pictures may include optional equipment and may not include all standard equipment. Equipment and options varies by regional availability.

TOUGH WORLD. TOUGH EQUIPMENT.

Electric Reach Truck

Main Features

COMFORTABLE AND BEAUTIFUL DESIGN

- Modern and new design in Modern design of control pedal, and the damping pedal with ergonomic design ensures comfortable driving.

MAST SYSTEM

- The mast has the reach forward function which allows the truck to store the goods without moving of the truck itself, which is convenient and safe; High quality imported C-shape mast ensures that the vehicle load capacity.

EMERGENCY BUTTON

- Safe and convenient configuration of the emergency button, emergency one-time cut off all energy, which greatly increase safety.



BUFFER SYSTEM FOR FORK LOWEING AND MAST FORWARD/BACKWARD

- Buffer system for fork loweing and mast forward/backward increase vehicle safety and operating comfort.

ELECTRONIC CONTROL FUNCTIONS

- The electrical energy, timing fault display is easy for operator to understand the vehicle condition and to have maintenance, The surface of electrical components is water and dust proof, the design of fully enclosed thermal of the central control unit to make the circuit more simple and reliable.



SPECIFICATION

Feature	Model	1		CLG2R015-M
	Power Type	2		Electric
	Driving Type	3		Standing
	Capacity	4	kg	1500
	Load Centre	5	mm	500
Dimension	Overall Length	6	mm	2246
	Overall Wide	7	mm	1130
	Height of the Overhead	8	mm	2330
	Forward Distance	9	mm	560
	Max. Lifting Height	10	mm	8000
	Overall Height	11		3398
	Max. Height of Truck	12	mm	8865
	Full Free Height	13	mm	2795
	Fork (Thickness×Wide×Length)	14	mm	35×100×920
	Fork Spread	15	mm	240-760
	Fork Tilted Angle	16	°	3 / 5
	Min. Gound Clearance	17	mm	80
	Aisle Wide 800×1000 pallet	18	mm	2695
	Tread Width	19	mm	1124
	Overhang	20	mm	180
Turning Radius	21	mm	1600	
Performance	Driving Speed (load / unload)	22	km/h	10.5 / 10.5
	Lifting Speed (load / unload)	23	mm/s	270 / 380
	Lowering Speed (load / unload)	24	mm/s	400 / 350
	Forward Speed (load / unload)	25	mm/s	100 / 100
	Max. Gradeability (load / unload)	26	%	10 / 15
Wheel	Front Wheel	27	mm	Φ267×135
	Driving Wheel	28	mm	Φ313×125
Motor	Driving Motor Power	29	kw	6.4
	Lifting Motor Power	30	kw	12.5
	Battery Capacity / Voltage	31	Ah/v	360 / 48
Weight	Service Weight	32	kg	3000
	Battery	33	kg	750

